

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.12.2018 Revision: 20.12.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: REVITAL Crack repair
- · **Article number:** 2.002.198
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages

PW Widespread use by professional workers

C Consumer use

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category PROC10 Roller application or brushing
- · Environmental release category ERC10a Widespread use of articles with low release (outdoor)
- · Application of the substance / the mixture

Façade paint

Dispersion paint/Latex paint

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

JUB d.o.o.

Dol pri Ljubljani 28

1262 DOL PRI LJUBLJANI

SLOVENIA

T: + 386 1 5884 183

F: + 386 1 5884 250

E: info@jub.si

· Further information obtainable from:

Laura Učakar

T: +386 1 5884 185

F: +386 1 5884 227

E: laura.ucakar@jub.eu

· 1.4 Emergency telephone number:

UK Emergency number: 999

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 20.12.2018 Revision: 20.12.2018

Trade name: REVITAL Crack repair

(Contd. of page 1)

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH208 Contains 2-octyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

The treated article incorporates biocidal products: 1,2-benzisothiazol-3(2H)-one, Pyrithione zinc, 2-methyl-2H-isothiazol-3-one, 2-octyl-2H-isothiazol-3-one, a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment Not applicable.
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Propylene glycol substance with a Community workplace exposure limit	>1-≤5%
	sodium hydroxide Met. Corr.1, H290; Skin Corr. 1A, H314	≤0.1%
CAS: 13463-41-7 EINECS: 236-671-3	Pyrithione zinc Acute Tox. 3, H301; Acute Tox. 3, H331 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10)	≤0.05%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

GB

Printing date 20.12.2018 Revision: 20.12.2018

Trade name: REVITAL Crack repair

(Contd. of page 2)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions:

In case of gas release or seepage into the ground inform responsible authorities.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients	with	limit	valuec	that	roauiro	manitarina	at the	worknlace
ingreatents	will	umu	ruiues	mui	equire	monnomi	ui iiic	workplace.

CAS: 57-55-6 Propylene glycol

WEL Long-term value: 474* 10** mg/m³, 150* ppm *total vapour and particulates **particulates

CAS: 1310-73-2 sodium hydroxide

WEL Short-term value: 2 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

(Contd. of page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.12.2018 Revision: 20.12.2018

Trade name: REVITAL Crack repair

protection:

· Eye protection:

Tightly sealed goggles

Goggles recommended during refilling

· Risk management measures

It is recommended to use high-quality work clothing and protective equipment. Use only outfits that meet the following standards:

- Protective gloves that meet the criteria of BS EN 374.
- Protective goggles must comply with standard BS EN 166.
- Protective mask respirator for fine dust particles and vapors should be in accordance with BS EN 143 (full face masks).

9.1 Information on basic physical and c	chemical properties
General Information	
Appearance: Form:	Viscous
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value at 20 °C:	8.5-9.5
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	$1.54-1.63 \text{ g/cm}^3$
Relative density	Not determined.
Vapour density	Not determined. Not determined.
Evaporation rate	woi determined.
Solubility in / Miscibility with water:	Not determined.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	19,000-28,000 mPas
Kinematic:	Not determined.
Solvent content:	<40.0 g/l
Organic solvents:	>1.4 %
Water:	7.3 %
VOC (EC)	2.60 %
Solids content:	68-75 %

Printing date 20.12.2018 Revision: 20.12.2018

Trade name: REVITAL Crack repair

(Contd. of page 4)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

	vant for classification: Estimates)
	<143,480 mg/kg (rat)
LC50/4 h	>69.242-86.12 mg/l (rat)
5-6 Propyl	lene glycol
LD50	2,000 mg/kg (rat)
LD50	20,800 mg/kg (rabbit)
-73-2 sodi	um hydroxide
LD50	2,000 mg/kg (rat)
3-41-7 Py	rithione zinc
LD50	269 mg/kg (rat)
LD50	>2,000 mg/kg (rat)
	>2,000 mg/kg (rabbit)
LC50/4 h	>2,000 mg/l (rabbit)
	LD50 LC50/4 h 5-6 Propyl LD50 LD50 -73-2 sodi LD50 63-41-7 Pyl LD50 LD50

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

	· Aquatic toxicity:
Ī	CAS: 1310-73-2 sodium hydroxide
	LC50/96 h $45 mg/l$ (/)

(Contd. on page 6)

Printing date 20.12.2018 Revision: 20.12.2018

Trade name: REVITAL Crack repair

	(Contd. of page 5)
CAS: 13463	3-41-7 Pyrithione zinc
LC50	0.028 mg/l (daphnia)
EC50/48 h	0.05 mg/l (daphnia)
EC50/72 h	0.067 mg/l (/)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- $\cdot \ \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

- European waste catalogue
 15 01 02 plastic packaging
- · Uncleaned packaging:
- Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.	
· UN "Model Regulation":	Void	

- GR

Printing date 20.12.2018 Revision: 20.12.2018

Trade name: REVITAL Crack repair

(Contd. of page 6)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Following regulation was considered in the preparation of document:

Legislation on the occupational health and safety, the chemical legislation and regulations on biocidal products, regulations on classification, packaging and labeling of chemical and biocidal products and requirements on safety data sheets for chemicals and biocidal products composition, as well as regulations on the management of packaging and packaging waste and waste.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Recommended restriction of use

Claims contained in this document are based on our actual knowledge at the time of revision of this document. They do not undertake the properties of the product described in terms of the legal provisions for the pledge.

Placing this document as available does not unbind the product customer from its responsibility to comply with all relevant laws and regulations applicable for this product. This is especially valid in the case of product resale or resale of its mixtures or manufactured products from other areas of law and industrial property rights of third parties. If the product described above is changed by crafting or mixing with other materials, it is not possible to transfer claims from this document onto a newly made product, unless otherwise specified. In the case of product re-packaging the customer must attach the required relevant safety information as well.

· Department issuing SDS:

JUB d.o.o.

Product safety department

· Contact:

Laura Učakar

laura.ucakar@jub.eu

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 3: Acute toxicity - Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

(Contd. on page 8)

Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.12.2018 Revision: 20.12.2018

Trade name: REVITAL Crack repair

(Contd. of page 7)

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.

GB -